

MV 1006

Modular Ice Machine up to 465 kg

Item #:
Project:
Quantity:



FEATURES

- “Global Standard” width- 30” (76 cm) wide.
- Auto-Alert indicator lights- communicate about operating status: a diagnostic LED light guides the troubleshooting process and helps decisions regarding opening a service call.
- Front-facing Evaporator - Ice forming process inspection and routine cleaning operations may be accomplished simply removing the front panel.
- Hand-removable water distribution tube- routine cleaning has never been so easy!
- Embedded antimicrobial- Ag-Ion® antimicrobial is present in selected food-zone components
- External Components- All external panel components are crafted for optimal aesthetic appeal through superior fit and finish.
- Reusable air filter is easily removable from the outside for ease of cleaning (in air-cooled models).



MV L 1006
Large Cube 17 g
W 29 x D 24 x H 29 mm



MV 1006
Dice Cube 10 g
W 22 x D 24 x H 22 mm



MV HL 1006
Half Large Cube 6 g
W 10 x D 24 x H 29 mm

CONDENSING SYSTEM

Air cooled
Water cooled

REFRIGERANT GAS

R404A

VOLTAGE V/Hz/ph

230/50/1
230/60/1
400/50/3

RECOMMENDED BINS

Head	Bins		kg
MV 1006	✓	SB393	181
	✓	SB530	243
	CBT42EMCD	SB550	252
	CBT48EAMCD	SB948	406
	CBT52EAMCD	SB1025	478
	●	UBH1100	553
●	UBH1600	812	

LEGEND:

- ✓ : Perfect combination between ice maker and bin
- : Ice chute cut-out performed upon installation
- CBTxxxxxxx : need additional bin top

Certifications:



OPERATING REQUIREMENTS

	Minimum	Maximum
Air temperature	10°C	43°C
Water temperature	5°C	38°C
Water pressure	1 bar (14 psi)	5 bar (70 psi)
Electrical voltage	-10%	+10%

IMPORTANT NOTICE:

Models and specifications are subject to change without notice. This spec sheet is meant for commercial purpose only. For technical documentation please refer to our service manuals.

Download our free **App Scotsman Ice**
 Apple store
 Google play
 Windows store



www.scotsman-ice.it
www.scotsman-ice.com


Modular Ice Machine up to 465 kg

MV 1006

Modular Ice Machine up to 465 kg

Item #:
Project:
Quantity:

Modular Ice Machine up to 465 kg



UNIT DATA	Compressor				Circuit wires		Max. fuse size
	Version	Voltage	Btu/h	W	No.	Ømm ²	A
Size (W x D x H)	760 x 620 x 800 mm						
Net weight	108 kg						
SHIPPING DATA	Carton (W x D x H)	830 x 690 x 870 mm					
	Weight	116 kg					
	MV 1006 AS	230/50/1	22943	6724	1		20
	MV 1006 WS	230/50/1	27533	8069	1		16
	MV 1006 WS	400/50/3	22619	6629	1		16
	MV HL 1006 AS	230/50/1	18497	5421	1		20
	MV HL 1006 WS	230/50/1	18497	5421	1		16
	MV L 1006 AS	230/50/1	18497	5421	1		20
MV L 1006 AS	400/50/3	18497	5421	1		16	
MV 1006 AS	230/60/1	27533	8069	1		20	
MV HL 1006 AS	230/60/1	18497	5421	1		20	

Version	Condensation	Voltage	24 h ice production kg			Energy consumption*		Water usage*	Instant power
			°C Amb. / °C Water			kWh/100 kg	kWh/24h		
			10°C/10°C	21°C/10°C	32°C/21°C			l/h	W
MV 1006 AS	Air	230/50/1	465	431	341	13.5	14.5	20.2	2550
MV 1006 WS	Water	230/50/1	415	405	360	10.6	11.4	208.0	2020
MV 1006 WS	Water	400/50/3	415	405	360	10.6	11.4	208.0	1950
MV HL 1006 AS	Air	230/50/1	465	431	341	13.5	13.2	20.2	2550
MV HL 1006 WS	Water	230/50/1	415	405	360	10.6	11.4	208.0	2020
MV L 1006 AS	Air	230/50/1	465	431	341	13.5	13.2	20.2	2500
MV L 1006 AS	Air	400/50/3	465	431	341	15.7	15.4	20.2	2350
MV 1006 AS	Air	230/60/1	465	431	341	12.5	13.5	20.2	2950
MV HL 1006 AS	Air	230/60/1	465	431	341	12.5	13.5	20.2	2950

(*) Data refer to 32°C Amb. / 21°C Water temperature conditions